

ECLIPSE 270 C6

◆ PRODUCT INTRODUCTION

ECLIPSE 270 C6 is a outstanding RGBALC 6 color profile, covering full color range. It is compated with CCS technology, precised CCT from 1800-10000K, reaching super high CRI ≥ 90 . ECLIPSE 270 C6 also has the perfect dimming curve and crystal-clear projection. It's designed for theater, opera, TV, rental and show applications!



◆ PRODUCT PARAMETERS

Optical system

Light source: 270W RGBALC

Luminous flux: 10276lm

CCT: 1800K-10000K

Angle: 5°/10°/14°/19°/26°/36°/50°/15°-30°/25°-50°

CRI RA/CRI R9/CQS/TLCI: 95/90/95/80

Work Environment

Ambient Temp: 0°C-45°C

IP Rated: IP20

Certification

CE, MET

Control System

Dimmer: 0-100% 16Bit

Cooling: Forced convection

Control: DMX512, RDM

Display: On board Control, 0-25Hz Strobe

Con Personality: BASIC (3CH), SSP (8CH), TOUR (13CH), TR16 (20CH),

HSIC (7CH), CMY (10CH)

Appearance

Size: 578 x 371 x 226mm

Weight: 8kg

Casing: Die-cast aluminum

Color: Black

Electrical Specs

Voltage: AC100-240V,50/60Hz

Rated Power: 280W


Power Connection: Power in and out

DMX XLR: 3pin or 5pin in and out


ECLIPSE 270 C6



ILLUMINANCE AT DISTANCE



DIMENSIONS



ACCESSORIES (Accessories not included unless otherwise stated)

